

## PRODUCT DATA SHEET

### ROLLED ZINC FOR BUILDING

(ROOFS, FAÇADES, RAINWATER GOODS, ETC.)

#### VEROZINC – VZ 110

Zn-Cu-Ti alloy in accordance with norm EN 988

### 1. DIMENSION TOLERANCES

DIMENSIONS	TOLERANCE
Thickness	± 0,03 mm
Width	+2 -0 mm
Length	+10 -0 mm
Lateral curvature	≤ 1,5 mm/m
Flatness	≤ 2 mm

### 2. MECHANICAL PROPERTIES (in the direction of rolling)

DESCRIPTION	GUARANTEED
Tensile Strength	≥ 150 N/mm <sup>2</sup>
Elongation	≥ 35 %
Bend test	No cracks on fold
Creep test	≤ 0,1 %

\* Dimensions, mechanical properties and chemical composition comply with Norm EN 988.

### 3. PRESENTATION

Sheets and coils in various thicknesses, widths and lengths.

# IEQSA

## 4. PACKAGING

Our products are wrapped in a specially formulated VCI paper. The products are arranged on wooden pallets and secured by straps. Additional security elements are also used, such as corner and edge protectors for zinc sheets or carton cores for zinc coils. Our pallets comply with ISPM 15.

